



# THE LOGICAL OPTION WHEN IT COMES TO GYM FLOORING.

## GYMlogix GYM FLOORING SPECIFICATIONS

### PRODUCT STANDARDS AND RESULTS

Item	Standard	Rating for Rolls and Tiles
Tensile Strength	ASTM D412	266 PSI
Density	ASTM D3676	69.2lbs./cubic foot
Tear Resistance	ASTM D413	Average Elongation at break 1.55
Hardness	ASTM D2240	Shore A 65 +/-5
Compression Set	ASTM D395	-4.90%
VOC Emissions	ASTM DS116	0.5 mg/m2 or less
Flammability	ASTM D2859	PASS
Resistance to Chemicals	F-925-02	Resistant to most acids and chlorine
Coefficient to Friction	ASTM D1894/5	>0.8


### GYM FLOORING DIMENSIONS-ROLLS

**Width:** Standard — 4'




**Thickness:** Standard — 3mm - 12mm

**Length:** Standard — 25' & 50'

Weight:	Thickness	Per sq ft
	6mm (1/4")	1.25 lb
	8mm (5/16")	1.65 lb
	9mm (3/8")	2 lb
	12mm (1/2")	2.5 lb
	19mm (3/4") Tiles only	4 lb



*Premium gym flooring available in rolls, tiles or mats. Can be interlocking or straight cut. Available in black, 10% color. Additional color percentage requires special ordering.*



RUBBERlogix color products are mixed to a set of guidelines put into place in our mixing line. However, we cannot control color shade changes in our EPDM supply. We strive to keep our color lines the same but cannot guarantee color across different batches.



Rolls available in 3mm, 4mm, 6mm, 8mm, 9mm & 12mm. Tiles are available in 6mm, 8mm, 9mm & 12mm. Custom widths are also available.