



**Manufactured by**  
***New River Tire Recycling***  
**312 East 52 Bypass**  
**Pilot Mountain, NC 27041**  
**(866) 465-6449**

Mesh Size	Average Weight Retained (g)	Percentage Retained (%)	Weight Range Specification
6	0g	0%	< 1%
8	7g	7.0%	5-15%
10	43g	43.0%	20-45%
14	27g	27.0%	20-35%
20	18g	18.0%	10-30%
30	5g	5.0%	0-10%
Pan	0g	0.0%	<1%

Product Test Sample Weight: 100-gram total weight  
 Length of test: 10 min in compliance with ASTM test standards

**PRODUCT DETAILS**

TYPE: Ambient ground styrene butadiene rubber (SBR)

ORIGIN: Recycled passenger and/or truck tires collected only within the U.S.A.

APPEARANCE: Solid black irregularly shaped granules of rubber-based materials

BULK DENSITY: 24.0 - 28.0 lbs./ft<sup>3</sup>

PACKAGING: 2,000 lb. supersacks with lift loops

**CERTIFICATION:**

Intertek Sustainability Certified Clean Air GOLD rating  
 Intertek’s Clean Air program independently tests and certifies products to low VOC standards that are recognized by sustainability initiatives including, but not limited to, LEED, WELL, and BIFMA e3. Conforms to California Department of Public Health (CDPH) Standard Method v1.2. TVOC range is less than 0.5 mg/m.

New River Tire Recycling Headquarters  
 312 East 52 Bypass Pilot Mountain, NC 27041  
 Phone 866-465-6449 or Email [sales@rubberlogix.com](mailto:sales@rubberlogix.com)